

High frequency + ATS design. Distortion:  $\leq 3\%$ , Efficiency:  $\geq 85\%$ , Regulation:  $\pm 2\%$ , Frequency: 50/60HZ  $\pm 1\%$  Output voltage adjustable, Green power function, Temperature control Fan, Input & Output isolated Input low & high voltage protection. Input & Output short circuit protection, Low battery alarm & shut-down, Overload protection, Temperature protection:  $50\pm 5$ , Fast Action AC Synchronised Transfer Switch (UPS Mode)

**Model Number**

**DC Input Available**

**Continue wattage**

**Surge power**

**Soft Start**

**R/C Port**

**No Load current**

**PM-600H**

**12/24Vdc**

**600W**

1800W

Y

Y

<1.5W

48Vdc

600W

1800W

Y

Y

<1.5W

PM-1000H

12/24Vdc

1000W

3000W

Y

Y

<1.5W

48Vdc

1000W

3000W

Y

Y

<1.5W

PM-1500H

12/24Vdc

1500W

4500W

Y

Y

<1.5W

48Vdc

1500W

4500W

Y

Y

<1.5W

**PM-3000H**

12/24Vdc

3000W

9000W

Y

Y

<1.5W

48Vdc

3000W

9000W

Y

Y

<1.5W

{adsense,pub-6522332961820161,9073834644,336,280,20}