

High frequency + ATS design. Distortion: $\leq 3\%$, Efficiency: $\geq 85\%$, Regulation: $\pm 2\%$, Frequency: 50/60HZ $\pm 1\%$ Output voltage adjustable, Green power function, Temperature control Fan, Input & Output isolated Input low & high voltage protection. Input & Output short circuit protection, Low battery alarm & shut-down, Overload protection, Temperature protection: 50 ± 5 , Fast Action AC Synchronised Transfer Switch (UPS Mode)

Model Number

DC Input Available

Continue wattage

Surge power

Soft Start

R/C Port

No Load current

PM-600H

12/24Vdc

600W

1800W

Y

Y

<1.5W

48Vdc

600W

1800W

Y

Y

<1.5W

PM-1000H

12/24Vdc

1000W

3000W

Y

Y

<1.5W

48Vdc

1000W

3000W

Y

Y

<1.5W

PM-1500H

12/24Vdc

1500W

4500W

Y

Y

<1.5W

48Vdc

1500W

4500W

Y

Y

<1.5W

PM-3000H

12/24Vdc

3000W

9000W

Y

Y

<1.5W

48Vdc

3000W

9000W

Y

Y

<1.5W

{adsense,pub-6522332961820161,9073834644,336,280,20}